

in the second states

1

## Bacterial Filtration Efficiency (BFE) Final Report

Test Article: Purchase Order: Study Number:	WLM2002 WL201906-1121T 1253866-S01
Study Received Date:	26 Dec 2019
Testing Facility:	Nelson Laboratories, LLC 6280 S. Redwood Rd.
	Salt Lake City, UT 84123 U.S.A.
Test Procedure(s): Deviation(s):	Standard Test Protocol (STP) Number: STP0004 Rev 18 None

**Summary:** The BFE test is performed to determine the filtration efficiency of test articles by comparing the bacterial control counts upstream of the test article to the bacterial counts downstream. A suspension of *Staphylococcus aureus* was aerosolized using a nebulizer and delivered to the test article at a constant flow rate and fixed air pressure. The challenge delivery was maintained at  $1.7 - 3.0 \times 10^3$  colony forming units (CFU) with a mean particle size (MPS) of  $3.0 \pm 0.3 \mu m$ . The aerosols were drawn through a six-stage, viable particle, Andersen sampler for collection. This test method complies with ASTM F2101-19 and EN 14683:2019, Annex B.

All test method acceptance criteria were met. Testing was performed in compliance with US FDA good manufacturing practice (GMP) regulations 21 CFR Parts 210, 211 and 820.

Test Side:InsideBFE Test Area:~40 cm²BFE Flow Rate:28.3 Liters per minute (L/min)Conditioning Parameters:85 ± 5% relative humidity (RH) and 21 ± 5°C for a minimum of 4 hoursTest Article Dimensions:~174 mm x ~154 mmPositive Control Average:1.8 x 10³ CFUNegative Monitor Count:<1 CFU</td>MPS:3.1 μm

			C-MRA	ACCREDITED
Curtis Derow	For	07	Jan	2020
Study Director	Janelle R. Bentz, M.S.	Study Cor	npletion	Date
	lsonlabs.com		hcb	FRT0004-0001 Rev 22 Page 1 of 2



## **Results:**

Test Article Number	Percent BFE (%)		
1	>99.9ª		
2	>99.9 <sup>a</sup>		
3	>99.9 <sup>a</sup>		
4	>99.9 <sup>a</sup>		
5	>99.9 <sup>a</sup>		

<sup>a</sup> There were no detected colonies on any of the Andersen sampler plates for this test article.

The filtration efficiency percentages were calculated using the following equation:

% 
$$BFE = \frac{C-T}{C} \times 100$$
  
C = Positive control average  
T = Plate count total recovered downstream of the test article  
Note: The plate count total is available upon request